


Общие рекомендации по сверлению

General recommendations for drilling

Données générales d'application pour le perçage

Диаметры свёрл под нарезание резьбы / Drill sizes before tapping / Diamètre de perçage avant taraudage



Трубная цилиндрическая резьба WHITWORTH G (BSP)
 Whitworth pipe thread DIN ISO 228
 Filetage Whitworth DIN ISO 22

Номинальный диаметр резьбы Thread Designation Référence du filetage	Наружный диаметр Diameter external Diamètre extérieur [Inch]	Наружный диаметр Diameter external Diamètre extérieur [mm]	Средний диаметр Diameter nut Diamètre nominal [mm]	Диаметр отверстия Bore diameter Diamètre de perçage [mm]	Шаг Pitches per Nombre de filets par [Inch]
G 1/8"	1/8	9,73	8,85	8,80	28
G 1/4"	1/4	13,16	11,89	11,80	19
G 3/8"	3/8	16,66	15,39	15,25	19
G 1/2"	1/2	20,95	19,17	19,00	14
G 5/8"	5/8	22,91	21,13	21,00	14
G 3/4"	3/4	26,44	24,66	24,50	14
G 7/8"	7/8	30,20	28,42	28,25	14
G 1"	1	33,25	30,93	30,75	11
G 1 1/8"	1 1/8	37,90	35,58	35,30	11
G 1 1/4"	1 1/4	41,91	39,59	39,25	11
G 1 3/8"	1 3/8	44,32	42,00	41,70	11
G 1 1/2"	1 1/2	47,80	45,48	45,25	11
G 1 3/4"	1 3/4	53,74	51,43	51,10	11
G 2"	2	59,61	57,29	57,00	11
G 2 1/4"	2 1/4	65,71	63,39	63,10	11
G 2 1/2"	2 1/2	75,18	72,86	72,60	11
G 2 3/4"	2 3/4	81,53	79,21	78,90	11
G 3"	3	87,88	85,56	85,30	11
G 3 1/4"	3 1/4	93,98	91,66	91,50	11
G 3 1/2"	3 1/2	100,33	98,01	97,70	11
G 3 3/4"	3 3/4	106,68	104,30	104,00	11
G 4"	4	113,03	110,71	110,40	11