



Teilprofil

Partial profile

Неполный профиль

55°

Außengewinde / External threading / Наружная резьба



Ausführung / Type / Тип:


Стандарт

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

Teilung Pitch Шар	Links Left Левая	Rechts Right Правая	d	r	x	y	Sorten / Grades / Сплавы			Klemmhalter Tool holder Державка
							AL100	AM7C	AM15C	
[mm] [ниток/дюйм]										
11 0,5-1,5 48-16		11ER-T-A55	6,35	0,05	0,8	0,9	●	●	●	● NL..-2
11 0,5-1,5 48-16	11EL-T-A55		6,35	0,05	0,8	0,9	●	●	●	● NL..-2
16 0,5-1,5 48-16		16ER-T-A55	9,525	0,05	0,8	0,9	●	●	●	● NL..-2
16 0,5-1,5 48-16	16EL-T-A55		9,525	0,05	0,8	0,9	●	●	●	● NL..-2
16 1,75-3,0 14-8		16ER-T-G55	9,525	0,21	1,2	1,7	●	●	●	● NL..-2
16 1,75-3,0 14-8	16EL-T-G55		9,525	0,21	1,2	1,7	●	●	●	● NL..-2
16 0,5-3,0 48-8		16ER-T-AG55	9,525	0,07	1,2	1,7	●	●	●	● NL..-2
16 0,5-3,0 48-8	16EL-T-AG55		9,525	0,07	1,2	1,7	●	●	●	● NL..-2
16 0,5-1,5 48-16		16ER-T-A55-SB	9,525	0,05	0,6	0,8	●			● AL..-3
16 1,75-3,0 14-8		16ER-T-G55-SB	9,525	0,21	1,1	1,5	●			● AL..-3
16 0,5-3,0 48-8		16ER-T-AG55-SB	9,525	0,07	0,9	1,5	●			● AL..-3

P	●	○	
M	●	●	●
K	○	○	
N			●
S	○		
H			

- **Hauptanwendung**
Main application
Основное применение
- **Nebenanwendung**
Secondary application
Вторичное применение



Ausführung / Type / Тип:

U

Teilung Pitch Шар	Links / Rechts Left / Right Левая / Правая	d	r	x	y	Sorten / Grades / Сплавы			Klemmhalter Tool holder Державка
						AL100	AM7C	AM15C	
[mm] [ниток/дюйм]									
22 5,5-8,0 4,5-3,25	22UEI-T-U55	12,7	0,60	0,9	11,0		●	●	● AL..-4U
27 6,5-9,0 4-2,75	27UEI-T-U55	15,88	0,80	1,2	13,7	●			● AL..-5U

P	●	○	
M	●	●	●
K	○	○	
N			●
S	○		
H			

- **Hauptanwendung**
Main application
Основное применение
- **Nebenanwendung**
Secondary application
Вторичное применение