

# Amerikanisches ISO-Zollgewinde

American thread  
Американская резьба

UN

## Außengewinde / External threading / Наружная резьба

Ausführung / Type / Тип:  
Стандарт

Teilung Pitch Шаг [нитек/дюйм]	Links Left Левая	Rechts Right Правая	d	h <sub>min</sub>	x	y	Sorten / Grades / Сплавы					Klemmhalter Tool holder Державка	
							beschichtet coated с покрытием			unbeschichtet uncoated без покрытия			
							AL100	AM7C	AM15C	AK20	AK20P		
16	36		16ER-V-UN36-SB	9,525	0,43	1,2	0,5	●					AL..-3
16	32		16ER-V-UN32-SB	9,525	0,49	1,2	0,5	●					AL..-3
16	28		16ER-V-UN28-SB	9,525	0,56	0,7	0,8	●					AL..-3
16	24		16ER-V-UN24-SB	9,525	0,65	0,7	0,8	●					AL..-3
16	20		16ER-V-UN20-SB	9,525	0,78	0,7	0,8	●					AL..-3
16	18		16ER-V-UN18-SB	9,525	0,87	0,7	0,8	●					AL..-3
16	16		16ER-V-UN16-SB	9,525	0,97	0,8	0,8	●					AL..-3
16	14		16ER-V-UN14-SB	9,525	1,11	1,2	1,5	●					AL..-3
16	13		16ER-V-UN13-SB	9,525	1,20	1,2	1,5	●					AL..-3
16	12		16ER-V-UN12-SB	9,525	1,30	1,3	1,5	●					AL..-3
16	10		16ER-V-UN10-SB	9,525	1,56	1,2	1,5	●					AL..-3
16	9		16ER-V-UN9-SB	9,525	1,73	1,2	1,5	●					AL..-3
16	8		16ER-V-UN8-SB	9,525	1,95	1,3	1,5	●					AL..-3
22	7		22ER-V-UN7	12,7	2,22	1,6	2,3	●	●	●	●		AL..-4
22	7	22EL-V-UN7		12,7	2,22	1,6	2,3	●	●	●			AL..-4
22	6		22ER-V-UN6	12,7	2,60	1,6	2,3	●	●	●	●		AL..-4
22	6	22EL-V-UN6		12,7	2,60	1,6	2,3	●	●	●			AL..-4
22	5		22ER-V-UN5	12,7	3,12	1,7	2,5	●	●	●	●	●	AL..-4
22	5	22EL-V-UN5		12,7	3,12	1,7	2,5	●	●	●	●		AL..-4
27	4,5		27ER-V-UN4.5	15,88	3,46	1,9	2,7	●	●	●	●		AL..-5
27	4,5	27EL-V-UN4.5		15,88	3,46	1,9	2,7	●					AL..-5
27	4		27ER-V-UN4	15,88	3,89	2,1	3,0		●	●	●		AL..-5
27	4	27EL-V-UN4		15,88	3,89	2,1	3,0				●		AL..-5

P	●		○	
M	●	●	●	
K	○		○	
N				
S	○			
H				

● Hauptanwendung  
Main application  
Основное применение

○ Nebenanwendung  
Secondary application  
Вторичное применение

5