



Kegeliges Rohrgewinde

Tapered pipe thread

Коническая трубная резьба

NPT

Außengewinde / External threading / Наружная резьба



Ausführung / Type / Тип:

Стандарт

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

Teilung Pitch Шаг	Links Left Левая	Rechts Right Правая	d	h _{min}	x	y	Sorten / Grades / Сплавы			unbeschichtet uncoated без покрытия		Klemmhalter Tool holder Державка
							AL100	AM7C	AM15C	AK20	AK20P	
11	18	11ER-V-NPT18	6,35	1,01	0,8	1,0			●			NL...-2
11	14	11ER-V-NPT14	6,35	1,33	0,8	1,0	●	●				NL...-2
11	14	11EL-V-NPT14	6,35	1,33	0,8	1,0			●			NL...-2
16	27	16ER-V-NPT27	9,525	0,66	0,7	0,8	●	●	●	●		AL...-3
16	27	16EL-V-NPT27	9,525	0,66	0,7	0,8			●	●		AL...-3
16	18	16ER-V-NPT18	9,525	1,01	0,8	1,0	●	●	●	●	●	AL...-3
16	18	16EL-V-NPT18	9,525	1,01	0,8	1,0	●	●	●	●		AL...-3
16	14	16ER-V-NPT14	9,525	1,33	0,9	1,2	●	●	●	●	●	AL...-3
16	14	16EL-V-NPT14	9,525	1,33	0,9	1,2	●	●	●	●		AL...-3
16	11,5	16ER-V-NPT11,5	9,525	1,64	1,1	1,5	●	●	●	●	●	AL...-3
16	11,5	16EL-V-NPT11,5	9,525	1,64	1,1	1,5	●	●	●	●	●	AL...-3
16	8	16ER-V-NPT8	9,525	2,42	1,3	1,8	●	●	●	●		AL...-3
16	8	16EL-V-NPT8	9,525	2,42	1,3	1,8	●		●			AL...-3
16	27	16ER-V-NPT27-SB	9,525	0,66	0,6	0,8	●					AL...-3
16	18	16ER-V-NPT18-SB	9,525	1,01	0,6	0,8	●					AL...-3
16	14	16ER-V-NPT14-SB	9,525	1,33	1,1	1,5	●					AL...-3
16	11,5	16ER-V-NPT11,5-SB	9,525	1,64	1,1	1,5	●					AL...-3
16	8	16ER-V-NPT8-SB	9,525	2,42	1,0	1,5	●					AL...-3

P	●		○		
M	●	●	●		
K	○		○		
N				●	●
S	○				
H					

● **Hauptanwendung**
Main application
Основное применение

○ **Nebenanwendung**
Secondary application
Вторичное применение