



Rundgewinde

Round thread
Круглая резьба

DIN 405

Außengewinde / External threading / Наружная резьба



Ausführung / Type / Тип:
Стандарт

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

Teilung Pitch Шарг [нитек/дюйм]	Links Left Левая	Rechts Right Правая	d	h _{min}	x	y	Sorten / Grades / Сплавы			Klemmhalter Tool holder Державка			
							beschichtet coated с покрытием			unbeschichtet uncoated без покрытия		AL100	AM7C
16	10		16ER-V-RD405/10	9,525	1,27	1,1	1,2	●	●	●	●		
16	10	16EL-V-RD405/10		9,525	1,27	1,1	1,2	●	●	●	●	●	AL..-3
16	8		16ER-V-RD405/8	9,525	1,59	1,4	1,3	●	●	●	●	●	AL..-3
16	8	16EL-V-RD405/8		9,525	1,59	1,4	1,3	●	●	●	●	●	AL..-3
16	6		16ER-V-RD405/6	9,525	2,12	1,5	1,7	●	●	●	●	●	AL..-3
16	6	16EL-V-RD405/6		9,525	2,12	1,5	1,7	●	●	●	●	●	AL..-3
22	6		22ER-V-RD405/6	12,7	2,12	1,5	1,7	●	●	●	●	●	AL..-4
22	6	22EL-V-RD405/6		12,7	2,12	1,5	1,7	●	●	●	●	●	AL..-4
22	4		22ER-V-RD405/4	12,7	3,18	2,2	2,3	●	●	●	●	●	AL..-4
22	4	22EL-V-RD405/4		12,7	3,18	2,2	2,3	●	●	●	●	●	AL..-4
27	4		27ER-V-RD405/4	15,88	3,18	2,2	2,3	●	●	●	●	●	AL..-5
27	4	27EL-V-RD405/4		15,88	3,18	2,2	2,3	●	●	●	●	●	AL..-5

P	●	○		
M	●	●	●	
K	○	○		
N			●	●
S	○			
H				

● Hauptanwendung
Main application
Основное применение

○ Nebenanwendung
Secondary application
Вторичное применение