



Rundgewinde

Round thread

Круглая резьба

DIN 20400

Innengewinde / Internal threading / Внутренняя резьба



Ausführung / Type / Тип:


Стандарт

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

Teilung Pitch Шаг [mm]	Links Left Левая	Rechts Right Правая	d	h _{min}	x	y	Sorten / Grades / Сплавы		Klemmhalter Tool holder Державка	
							AL100	AM15C		
22	3,0		22IR-V-RD20400/3	12,7	1,65	1,3	1,7	●	●	AVR..-4
22	4,0		22IR-V-RD20400/4	12,7	2,20	1,6	2,2	●	●	AVR..-4
22	4,0	22IL-V-RD20400/4		12,7	2,20	1,6	2,2	●	●	AVR..-4
22	5,0		22IR-V-RD20400/5	12,7	2,75	1,4	1,7	●	●	AVR..-4
22	5,0	22IL-V-RD20400/5		12,7	2,75	1,4	1,7	●	●	AVR..-4
22	6,0		22IR-V-RD20400/6	12,7	3,30	1,7	2,1	●	●	AVR..-4
22	6,0	22IL-V-RD20400/6		12,7	3,30	1,7	2,1	●	●	AVR..-4

P	●	○
M	●	●
K	○	
N		
S	○	
H		

- **Hauptanwendung**
Main application
Основное применение
- **Nebenanwendung**
Secondary application
Вторичное применение



Ausführung / Type / Тип:

U

Teilung Pitch Шаг [mm]	Links / Rechts Left / Right Левая / Правая	d	h _{min}	x	y	Sorten / Grades / Сплавы		Klemmhalter Tool holder Державка
						AL100		
27	8,0	27UIN-V-RD20400/8	15,88	4,40	2,9	13,5	●	AL..-5U

P	●
M	●
K	○
N	
S	○
H	

- **Hauptanwendung**
Main application
Основное применение
- **Nebenanwendung**
Secondary application
Вторичное применение