



Spitzgewinde (DIN 5855)

MJ threads (DIN 5855)

Метрическая с MJ-профилем

MJ**Außengewinde / External threading / Наружная резьба****Ausführung / Type / Тип:****Стандарт**


Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

								Sorten / Grades / Сплавы				
	Teilung	Links	Rechts	d	h _{min}	x	y	beschichtet coated с покрытием			unbe- schichtet uncoated без покрытия	Klemmhalter Tool holder Державка
	Pitch	Left	Right					AL100	AM7C	AM15C		
	Шаг	Левая	Правая									
	[mm]											
16	0,7		16ER-V-MJ0,70	9,525	0,40	0,6	0,6			●		AL...-3
16	1,0		16ER-V-MJ1,00	9,525	0,58	0,7	0,7	●		●	●	AL...-3
16	1,0	16EL-V-MJ1,00		9,525	0,58	0,7	0,7	●		●		AL...-3
16	1,25		16ER-V-MJ1,25	9,525	0,72	0,8	0,9	●	●	●	●	AL...-3
16	1,25	16EL-V-MJ1,25		9,525	0,72	0,8	0,9	●		●		AL...-3
16	1,5		16ER-V-MJ1,50	9,525	0,87	0,8	1,0	●	●	●	●	AL...-3
16	1,5	16EL-V-MJ1,50		9,525	0,87	0,8	1,0	●		●		AL...-3
16	2,0		16ER-V-MJ2,00	9,525	1,15	1,0	1,3	●		●		AL...-3
16	2,0	16EL-V-MJ2,00		9,525	1,15	1,0	1,3	●		●		AL...-3
16	2,5		16ER-V-MJ2,50	9,525	1,49	1,1	1,5	●		●		AL...-3
16	2,5	16EL-V-MJ2,50		9,525	1,49	1,1	1,5	●		●		AL...-3
16	3,0		16ER-V-MJ3,00	9,525	1,73	1,2	1,6			●		AL...-3
16	3,0	16EL-V-MJ3,00		9,525	1,73	1,2	1,6			●		AL...-3

P	●		○
M	●	●	●
K	○	○	
N			●
S	○		
H			

● Hauptanwendung
Main application
Основное применение

○ Nebenanwendung
Secondary application
Вторичное применение

**Ausführung / Type / Тип:****Slim Throat / Slim Throat / Зауженные**

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

										Sorten / Grades / Сплавы		Klemmhalter Tool holder Державка
	Teilung Pitch Шаг	Links Left Левая	Rechts Right Правая	d	h _{min}	x	y	t	AL100	AM15C		
[mm]												
11	0,7		11VER-V-MJ0,70	6,35	0,40	0,7	2,5	3,2	●		NL...-2V	
11	0,7	11VEL-V-MJ0,70		6,35	0,40	0,7	2,5	3,2	●		NL...-2V	
11	0,8		11VER-V-MJ0,80	6,35	0,44	0,7	2,5	3,2	●	●	NL...-2V	
11	0,8	11VEL-V-MJ0,80		6,35	0,44	0,7	2,5	3,2	●		NL...-2V	
11	0,9		11VER-V-MJ0,90	6,35	0,53	0,7	2,6	3,2	●		NL...-2V	
11	0,9	11VEL-V-MJ0,90		6,35	0,53	0,7	2,6	3,2	●		NL...-2V	
11	1,0		11VER-V-MJ1,00	6,35	0,58	0,7	2,5	3,2	●		NL...-2V	
11	1,0	11VEL-V-MJ1,00		6,35	0,58	0,7	2,5	3,2	●		NL...-2V	

P	●		○
M	●	●	●
K	○		
N			●
S	○		
H			

● Hauptanwendung
Main application
Основное применение

○ Nebenanwendung
Secondary application
Вторичное применение