



Metrisches Sägewinde (DIN 513)

Buttres thread
Упорная резьба

SAGE

Außengewinde / External threading / Наружная резьба



Ausführung / Type / Тип:
Стандарт

Rechte Ausführung abgebildet / Right-hand execution shown / Показано правостороннее исполнение

										Sorten / Grades / Сплавы				
	Teilung	Links	Rechts	d	h _{min}	x	y	beschichtet coated с покрытием			unbe- schichtet uncoated без покрытия	Klemmhalter Tool holder Державка		
	Pitch Шар	Left Левая	Right Правая					AL100	AM7C	AM15C	AK20			
[mm]														
16	2,0		16ER-V-SAGE2,0	9,525	1,74	1,5	2,1	●	●	●	●	AL...-3		
16	2,0	16EL-V-SAGE2,0		9,525	1,74	1,5	2,1	●		●	●	AL...-3		
22	2,0		22ER-V-SAGE2,0	12,7	1,74	1,5	2,1	●		●		AL...-4		
22	3,0		22ER-V-SAGE3,0	12,7	2,60	1,8	2,6	●	●	●	●	AL...-4		
22	3,0	22EL-V-SAGE3,0		12,7	2,60	1,8	2,6	●		●		AL...-4		
22	4,0		22ER-V-SAGE4,0	12,7	3,55	1,75	3,1	●		●		AL...-4		
22	4,0	22EL-V-SAGE4,0		12,7	3,55	1,75	3,1			●		AL...-4		
27	4,0		27ER-V-SAGE4,0	15,88	3,55	1,9	3,2	●	●	●		AL...-5		
27	4,0	27EL-V-SAGE4,0		15,88	3,55	1,9	3,2	●	●		●	AL...-5		

P	●		○		● Hauptanwendung Main application Основное применение
M	●	●		●	
K	○		○		○ Nebenanwendung Secondary application Вторичное применение
N					
S	○				
H					